


DESIGN

Product Type:	Glue Down LVT
Overall Thickness:	2.5 mm (.1")
Wear Layer:	20 mil (0.5 mm)
Finish:	M-Force
Size:	152.4mm x 1219.2mm (actual) 6"W x 48"L (nominal)
Square Feet Per Carton:	36 sf/ctn (3.34 m ² /ctn)
Pieces Per Carton:	60 cartons/pallet
Pounds Per Carton:	29.7 lbs/ctn
Installation Method:	Glue Down
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, M99 Resilient Flooring Adhesive, or M700 Adhesive
Underlayment:	Mohawk AccuSound™ (Optional)

SUSTAINABILITY

Certification:	FloorScore® certified
----------------	-----------------------

PERFORMANCE

Construction:	Commercial Grade Luxury Vinyl Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size And Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Thickness:	ASTM F386 - Passes - As Specified ±0.005 in.
Flexibility:	ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
Dimensional Stability:	ASTM F2199 - Passes - ≤ 0.020 in. per linear foot
Static Load:	ASTM F970 - Passes, modified - 1000 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E662 Part A - Passes - < 450

SERVICE

Warranties:	Limited 20-Year M-Force Ultra Commercial LVT Warranty
-------------	---



W123
Western Woods