



250
Dusty Trail
Quickship Available

DESIGN

Product Type:	Glue Down LVT
Overall Thickness:	2.5 mm
Wear Layer:	20 mil (0.5 mm)
Finish:	M-Force Ultra
Size:	12"W x 24"L
Square Feet Per Carton:	36 sf/ctn
Pieces Per Carton:	18 pieces/ctn
Pounds Per Carton:	30.64 lbs/ctn
Installation Method:	Glue Down

SUSTAINABILITY

Certification:	FloorScore® certified
Certification Detail:	Utilizes 100% closed-loop pre-consumer recycled content allocation
Country Of Origin:	Made In USA

PERFORMANCE

Construction:	Commercial Grade Luxury Vinyl Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F 2421 - Passes - ± 0.10 " max
Size And Tolerance:	ASTM F2421 - Passes - ± 0.016 "/linear foot
Thickness:	ASTM F386 - Passes - as specified ± 0.005 "
Flexibility:	ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - 0.020"/linear foot max
Static Load:	ASTM F970 - Passes, modified at 1000 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
Slip Resistant:	ASTM C1028 - Passes Wet: ≥ 0.5
Resistance To Chemicals:	ASTM F925 - Passes - No more than a slight change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E < 8$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E < 8$
Critical Radiant Flux:	ASTM E648 - Class 1 (> 0.45 W/cm ²)
Smoke Density:	ASTM E662 Part A - Less than 450

SERVICE

Warranties:	Limited 20 Year M-Force Ultra Commercial Warranty
-------------	---